



Erosion Logs



Photo Source: Colorado Department of Transportation



02-0201-11



Erosion Logs



Photo Source: Colorado Department of Transportation



02-0201-11



Erosion Logs



Photo Source: Colorado Department of Transportation



02-0201-11



Erosion Logs



Photo Source: Colorado Department of Transportation



02-0201-11

Erosion Logs

One of the water quality Best Management Practices (BMPs) available for erosion control during CDOT highway construction is erosion logs. These are manufactured products filled with rock or other filter material. This is a temporary BMP that can be used for check dams in ditches until vegetation cover is established. When erosion logs are used upstream of curb inlets or at curb inlet entrances, they serve as erosion control BMPs. This BMP is not appropriate for use in a ditch or swale with continuous water flow.

Proper maintenance for this BMP includes: daily inspection for cuts and abrasions; repositioning or replacement as necessary; and removal or proper disposal of sediment.

Guidance: CDOT Erosion Control and Stormwater Quality Guide, Chapter 5



Erosion Logs

One of the water quality Best Management Practices (BMPs) available for erosion control during CDOT highway construction is erosion logs. These are manufactured products filled with rock or other filter material. This is a temporary BMP that can be used for check dams in ditches until vegetation cover is established. When erosion logs are used upstream of curb inlets or at curb inlet entrances, they serve as erosion control BMPs. This BMP is not appropriate for use in a ditch or swale with continuous water flow.

Proper maintenance for this BMP includes: daily inspection for cuts and abrasions; repositioning or replacement as necessary; and removal or proper disposal of sediment.

Guidance: CDOT Erosion Control and Stormwater Quality Guide, Chapter 5



Erosion Logs

One of the water quality Best Management Practices (BMPs) available for erosion control during CDOT highway construction is erosion logs. These are manufactured products filled with rock or other filter material. This is a temporary BMP that can be used for check dams in ditches until vegetation cover is established. When erosion logs are used upstream of curb inlets or at curb inlet entrances, they serve as erosion control BMPs. This BMP is not appropriate for use in a ditch or swale with continuous water flow.

Proper maintenance for this BMP includes: daily inspection for cuts and abrasions; repositioning or replacement as necessary; and removal or proper disposal of sediment.

Guidance: CDOT Erosion Control and Stormwater Quality Guide, Chapter 5



Erosion Logs

One of the water quality Best Management Practices (BMPs) available for erosion control during CDOT highway construction is erosion logs. These are manufactured products filled with rock or other filter material. This is a temporary BMP that can be used for check dams in ditches until vegetation cover is established. When erosion logs are used upstream of curb inlets or at curb inlet entrances, they serve as erosion control BMPs. This BMP is not appropriate for use in a ditch or swale with continuous water flow.

Proper maintenance for this BMP includes: daily inspection for cuts and abrasions; repositioning or replacement as necessary; and removal or proper disposal of sediment.

Guidance: CDOT Erosion Control and Stormwater Quality Guide, Chapter 5

