

Stabilized Construction

Photo Source: Colorado Department of Transportation

02-0207-11

Stabilized Construction

Photo Source: Colorado Department of Transportation

02-0207-11

Stabilized Construction

Photo Source: Colorado Department of Transportation

02-0207-11

Stabilized Construction

Photo Source: Colorado Department of Transportation

02-0207-11

Stabilized Construction

One of the water quality Best Management Practices (BMPs) available for sediment control during CDOT highway construction is a stabilized construction entrance. This BMP consists of a stabilized layer of aggregate underlined with a geotextile, which is located where equipment enters or exits the construction site.

This stabilized area should be a minimum of 12 feet wide and 70 feet long. It should cover the entire width of the ingress/egress area.

The purpose of this temporary BMP is to reduce the amount of mud tracked out onto the paved public roads.

Guidance: CDOT Erosion Control and Stormwater Quality Guide, Chapter 5



Stabilized Construction

One of the water quality Best Management Practices (BMPs) available for sediment control during CDOT highway construction is a stabilized construction entrance. This BMP consists of a stabilized layer of aggregate underlined with a geotextile, which is located where equipment enters or exits the construction site.

This stabilized area should be a minimum of 12 feet wide and 70 feet long. It should cover the entire width of the ingress/egress area.

The purpose of this temporary BMP is to reduce the amount of mud tracked out onto the paved public roads.

Guidance: CDOT Erosion Control and Stormwater Quality Guide, Chapter 5



Stabilized Construction

One of the water quality Best Management Practices (BMPs) available for sediment control during CDOT highway construction is a stabilized construction entrance. This BMP consists of a stabilized layer of aggregate underlined with a geotextile, which is located where equipment enters or exits the construction site.

This stabilized area should be a minimum of 12 feet wide and 70 feet long. It should cover the entire width of the ingress/egress area.

The purpose of this temporary BMP is to reduce the amount of mud tracked out onto the paved public roads.

Guidance: CDOT Erosion Control and Stormwater Quality Guide, Chapter 5



Stabilized Construction

One of the water quality Best Management Practices (BMPs) available for sediment control during CDOT highway construction is a stabilized construction entrance. This BMP consists of a stabilized layer of aggregate underlined with a geotextile, which is located where equipment enters or exits the construction site.

This stabilized area should be a minimum of 12 feet wide and 70 feet long. It should cover the entire width of the ingress/egress area.

The purpose of this temporary BMP is to reduce the amount of mud tracked out onto the paved public roads.

Guidance: CDOT Erosion Control and Stormwater Quality Guide, Chapter 5

